


Ø458

Name	Height	Vol	Weight
JM-H-H2472-4T4B	2150mm	471 L	



NOTES:

- 1. Inner shell Polyethylene (PE) seamless one-piece tank liner
- 2. Outer shell Continuous strands of fiber-glass with high strength epoxy resin
- 3. Bottom base FRP reinforced tripod base
- 4. Opening 4 inch thread opening
- 5. Tanks meet all applicable specification of NSF/ANSI 044 standard
- 6. Operating Specifications:

Maximum Working Pressure : 150 PSI (1.0MPA)

Temperature :1-49 C (34-120 F)

Maximum Vacuum:127mm Hg(5"Hg)

7. Liner inspection

No more than 20 internal 、external blemishes、burnt debris

No internal 、external blemishes、burnt debris larger than 5 *5 mm

- 8. Surface finish
- 9. Surface to be free of resin, glass, nicks, barbed filament
- 10. Tank to be bonded to base
- 11. The base to be level correction
- 12. Top and bottom opening to be parallel top opening to be parallel with the base

		388		4 3 2 1 NC		4-8UN LINER OUTER S BASE	SHEEL			2 1 1 1 COUNT	PE FRP SMC	MA	FIED PP	REMARK
φ ₆	Ø600		标记	处数	分区	更改文件号	签名	日期	FZC		Int	erna	ational	Trading
		•	设计			标准化			阶段	没标记	重量(Kg)	比例		
			审核	检测人	、检测日	期			本图尺寸	均以mm计	,图中尺:	计请勿量 耳	ДМ-Н-Н24	172-4T4B