







NOTES:

- 1. Inner shell Polyethylene (PE) seamless one-piece tank liner
- 2. Outer shell Continuous strands of fiber-glass with high strength epoxy resin
- 3. Bottom base FRP reinforced tripod base
- 4. Opening 4 inch thread opening
- 5. Tanks meet all applicable specification of NSF/ANSI 044 standard
- 6. Operating Specifications:

Maximum Working Pressure : 150 PSI (1.0MPA)

Temperature :1-49 C (34-120 F) Maximum Vacuum:127mm Hg(5"Hg)

7. Liner inspection

No more than 20 internal cexternal blemishes burnt debris No internal sexternal blemishes burnt debris larger than 5 *5 mm

- 8. Surface finish
- 9. Surface to be free of resin, glass, nicks, barbed filament
- 10. Tank to be bonded to base
- 11. The base to be level correction
- 12. Top and bottom opening to be parallel,top opening to be parallel with the base

					3		Linner		1		ı	PE		
					2		OuterShell			1	I	-RP		
					1		Base			1		SMC		
					NO.		NAME			COUNT		MATERIAL	REMARK	
				Ц.	Subsidiary Column									
				1				Jieming International Trading FZCO Ewater						
	标记	处数	分包	< .	更改文件号	签名	日期	cwate	er					
	设计		\bot		标准化			阶段标记	5	重量(Kg)	比例			
			_					ПТ						
	审核 检测人		1 16	注測日期				本图尺寸均以	以mm计,图中尺寸请约		 十请勿量耳	,ЈМ-Н-НЗ	672-4T4B	

4"-8UN

PPO

